(19) World Intellectual Property Organization International Bureau



(43) International Publication Date 3 February 2005 (03.02.2005)

(10) International Publication Number WO 2005/010896 A1

(51) International Patent Classification7: C08L 23/04, H01B 7/00, 17/62

H01B 3/44.

(21) International Application Number:

PCT/US2004/023723

(22) International Filing Date: 22 July 2004 (22.07.2004)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data: 60/490,314

24 July 2003 (24.07.2003)

- (71) Applicant (for all designated States except US): UNION CARBIDE CHEMICALS & PLASTIC TECHNOL-OGY CORPORATION [US/US]; 39 Old Ridgebury

- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,

OGY CORPORATION [US/US]; 39 Old Ridgebury Road, Danbury, CT 06817-0001 (US).

(72) Inventor; and
(73) Inventor; and
(74) Agent: HANSBRO, Kevin, R.; The Dow Chemical Company, Intellectual Property, P.O. Box 1967, Midland, MI 48641-1967 (US).

(84) Title: CABLE INSULATION SYSTEM WITH FLEXIBILITY, HIGH TEMPERATURE DEFORMATION RESISTANCE, AND REDUCED DEGREE OF STICKINESS

(87) Abstract: The present invention is a cable comprising one or more electrical conductors or a core of one or more electrical conductors and having each conductor or core being surrounded by a layer of insulation. The insulation comprises an olefinic polymer, having a density in the range of 0.880 to 0.915 grams per cubic centimeter, a melting temperature of at least 115 degrees Celsius, a melt index in the range of 0.5 to 10 grams per 10 minutes, a crystallization-analysis-soluble fraction in 1.2 A and the company of the property of the present invention is a cable comprising one or more electrical conductors or a core of one or more electrical conductors or a core of one or more electrical conductors or a core of one or more electrical conductors or a core of one or more electrical conductors or a core of one or more electrical conductors or a core of one or more electrical conductors and having each conductor or core being surrounded by a layer of insulation. The insulation comprises an olefinic polymer, having a density in the range of 0.880 to 0.915 grams per cubic centimeter, a melting temperature of at least 115 degrees Celsius, a melt index in the range of 0.5 to 10 grams per 10 minutes, a crystallization-analysis-soluble fraction in 1.2 A and the conductors of the PCT Grammer. a melt index in the range of 0.5 to 10 grams per 10 minutes, a crystallization-analysis-soluble fraction in 1,2,4-trichlorobenzene at 30 degrees Celsius of less than 35 weight percent, and a polydispersity index of at least 3.5. Alternatively, the insulation layer has an 1% secant flexural modulus at ambient of less than 15,000 psi and a dynamic elastic modulus at 150 degrees Celsius of at least 4x10⁷ dyne/square centimeter.

